

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address COMMISSIONER FOR PATENTS PO Box 1450 Alcassedan, Virginia 22313-1450 www.emplo.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO	
10/701,029	11/04/2003	Brian Grove	G&C 30074.50-US-U1	6164	
29773 7590 04082009 DRINKER BIDDLE & REATH ATTN: INTELLECTUAL PROPERTY GROUP ONE LOGAN SQUARE 18TH AND CHERRY STREETS PHILADELPHIA, PA 19103-6996			EXA	EXAMINER	
			SHIFERAW, ELENI A		
			ART UNIT	PAPER NUMBER	
			2436	•	
			MAIL DATE	DELIVERY MODE	
			04/08/2009	PAPER	

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Examiner-Initiated Interview Summary	10/701,029	GROVE ET AL.				
Examiner-induced interview duminary	Examiner	Art Unit				
	ELENI A. SHIFERAW	2436				
All Participants: Status of Application:						
(1) <u>ELENI A. SHIFERAW</u> . (3)						
(2) Gregory J. Lavorgna.	(4)					
Date of Interview: <u>1 April 2009</u>	Time:					
Type of Interview: ⊠ Telephonic □ Video Conference □ Personal (Copy given to: □ Applicant Exhibit Shown or Demonstrated: □ Yes □ No If Yes, provide a brief description:	ant's representative)					
,						
Part I. Rejection(s) discussed:						
rejection(s) discussed.						
Claims discussed:						
Prior art documents discussed:						
Part II.						
SUBSTANCE OF INTERVIEW DESCRIBING THE GENE See Continuation Sheet	RAL NATURE OF WHAT WAS	S DISCUSSED:				
Part III.						
☐ It is not necessary for applicant to provide a separate record of the substance of the interview, since the interview directly resulted in the allowance of the application. The examiner will provide a written summary of the substance of the interview in the Notice of Allowability. It is not necessary for applicant to provide a separate record of the substance of the interview, since the Interview did not result in resolution of all issues. A brief summary by the examiner appears in Part II above.						
/Eleni A Shiferaw/ Examiner, Art Unit 2436	Applicant/Applicant's Representat	ive Signature – if appropriate)				

Application No.

Applicant(s)

Application No. 10/701,029

Continuation of Substance of Interview including description of the general nature of what was discussed: The examiner contacted the applicant's undersigned attorney Gregory J. Lavorgna to move the case forward by providing proposed amendment as follows below, Mr. Lavorgna called back on 4/2/09 and said the inventor thinks it will narrow the invention since there might be some more unique characteristics in the feature and it will limit the inventor from those feature unique characteristics. The examiner's intention was to expedite the prosecution and move the case forward.

34. (Currently Amended) A method of authenticating a hardware token for operation with a host, comprising: retrieving a value X from a memory separate from the hardware token accessible to an authenticating entity, the value X generated from a non-varying computer fingerprint F of the host and an identifier P securing access to the hardware token, wherein the host fingerprint F is a hash of concatenated computed at least in part from non-varying host information C based on a unique characteristic of the host and a server specific value V transmitted from the server, to authenticate the hardware token:

aumenticate the hardware loken; where it is not maken to include a host processor serial or model number, hard disk serial or model number, a network interface MAC address or unique serial number burned into Ethernet and token ring adaptor, basic input otiputs system code area checksum and operating system type or version;

wherein the value X is computed in the hardware token, according to $\dot{X} = f(P, F)$, wherein f(P, F) is a reversible function such that f(f(P, F), F) = P, wherein f(P, F) further comprises P XOR F, and stored in the host;

re-computing the fingerprint F;

regenerating the same identifier value P for the hardware token at least in part from the retrieved value X and the recomputed fingerprint F; and

transmitting the regenerated identifier P to the hardware token to unlock authenticate the hardware token for operation with the bost

- 36. (Canceled)
- 38. (Canceled)
- 39. (Canceled)
- (Canceled)
- (Currently amended) The method of claim 34, wherein:

the authorizing entity is a host computer communicatively coupleable to the hardware token; and the value X is stored in the host computer.

45. (Currently amended) The method of claim 34, wherein the value X is stored in a memory accessible to the authentication entity by performing steps comprising the steps of: computing a reference value H associated with the value X: and

associably storing the value X and the reference value H in a memory of the hardware token.

- 48. (Currently Amended) The method of claim 45, wherein the reference value H is computed at least in part from [[a]] the hash of the fingerprint F.
- 49. (Currently Amended) An apparatus for authenticating a hardware token for operation with a host, comprising: a memory:

means for retrieving a value X from [[a]] the memory separate from the hardware token accessible to an authenticating entity, the value X generated from a non-varying computer fingerprint F of the host and an identifier P securing access to the hardware token, wherein the host fingerprint F is a hash of concatenated computed at least in part from non-varying host information C based on a unique characteristic of the host and a server specific value V transmitted from the server, to authenticate the hardware token:

wherein the concatenated non-varying host information C includes a host processor serial or model number, hard disk serial or model number, a network interface MAC address or unique serial number burned into Ethernet and token ring adaptor, basic input output system code area checksum and operating system type or version;

wherein the value X is computed in the hardware token, according to X = f(P, F), wherein f(P, F) is a reversible function such that f(f(P, F), F) = P, wherein f(P, F) further comprises P XOR F, and stored in the host;

re-computing the fingerprint F;

means for regenerating the same identifier value P for the hardware token at least in part from the retrieved value X and the re-computed fingerprint F; and

means for transmitting the regenerated identifier P to the hardware token to unlock authenticate the hardware token for operation with the host.

- 51. (Canceled)
- 53. (Canceled)
- 54. (Canceled) 55
- (Canceled)
- 59. (Currently amended) The apparatus of claim 49, wherein:

the authorizing entity is a host computer communicatively coupleable to the hardware token; and the value X is stored in the host computer.

60. (Currently amended) The apparatus of claim 49, wherein the value X is stored in a memory of the hardware token, and wherein the hardware token further comprises:

means for computing a reference value H associated with the value X; and

means for associably storing the value X and the reference value H in a memory of the hardware token.

(Currently Amended) The apparatus of claim 60, wherein the reference value H is computed at least in part from [[a]] the hash of the fingerprint F. (Currently Amended) An apparatus for authenticating a hardware token for operation with a host, the

Application No. 10/701,029

apparatus comprising a processor and a memory storing instructions for performing steps comprising the steps of: retrieving a value X from a memory separate from the hardware token accessible to an authenticating entity, the value X generated from a non-yawing computer fingerprint F of the host and an identifier P securing access to the hardware token, wherein the host fingerprint F is a hash of concatenated computed at least in part from non-varying host information C based on a unique characteristic of the host and a server specific value V

transmitted from the server, to authenticate the hardware token; wherein the concatenated non-varying host information C includes a host processor serial or model number, hard disk serial or model number, a network interface MAC address or unique serial number burned into Ethernet and token ring adaptor, basic input output system code area checksum and operating system type or version;

wherein the value X is computed in the hardware token, according to X = f(P, F), wherein f(P, F) is a reversible function such that f(f(P, F), F) = P, wherein f(P, F) further comprises P XOR F, and stored in the host;

re-computing the fingerprint F;

regenerating the same identifier value P for the hardware token at least in part from the retrieved value X and the recomputed fingerprint F; and

transmitting the regenerated identifier P to the hardware token to unlock authenticate the hardware token for operation with the host.

- 66. (Canceled)
- 68. (Canceled)
- 69 (Canceled)
- 70. (Canceled)
- 74. (Currently amended) The apparatus of claim 64, wherein:

the authorizing entity is a host computer communicatively coupleable to the hardware token; and the value X is stored in the host computer.

75. (Currently amended) The apparatus of claim 64, wherein the value X is stored in a memory of the hardware token, and the processing steps further comprise the steps of: computing a reference value H associated with the value X; and

associably storing the value X and the reference value H in a memory of the hardware token.

78. (Currently amended) The apparatus of claim 75, wherein the reference value H is computed at least in part from [[a]] the hash of the fingerprint F.